

CLAIMS

Sub
H/1

1. An image pickup device equipped with a light emitter, comprising:
- an image pickup unit for picking up an image and converting the picked-up image into an electric signal;
 - a memory for storing data electrically converted by the image pickup unit;
 - a determining section for making a determination of whether the electric signal converted by the image pickup unit has a proper brightness or not;
 - a controller for making the electric signal converted by the image pickup unit to be stored in the memory if a result of the determination of the determining section is "proper"; and
 - a light emitter for being controlled by the controller to emit light in timing with an image pickup timing of the image pickup device.
2. An image pickup device according to claim 1, wherein
- when a result of the determination of the determining section is "not proper", the controller obtains a light quantity of the light emitter which is assumed to be "proper" based on the electric signal converted by the image pickup unit, dispatches an image pickup instruction again to the image pickup unit, and at the same time, controls the light emitter to emit light in timing with the image pickup timing.

3. An image pickup device according to claim 1,
wherein

the controller prohibits a storing of the electric
signal converted by the image pickup unit which has
5 been determined as "not proper", in the memory.

4. An image pickup device according to claim 3,
wherein

when an electric signal converted by the image
pickup unit in timing with a first light emission of
the light emitter is "not proper", the controller makes
10 the memory to store electric signals converted by the
image pickup unit in timing with second and subsequent
light emissions of the light emitter.

5. An image pickup device equipped with a strobe,
15 comprising:

an image pickup unit which is a so-called charge
coupled device (CCD), for picking an image of an object
and converting this image into an electric signal;

a memory for storing data electrically converted
20 by the image pickup unit;

a determining section in a CPU for making a
determination of whether the electric signal converted
by the image pickup unit is a proper image or not;

a controller in the CPU for making the electric
25 signal converted by the image pickup unit to be stored
in the memory if a result of the determination of the
determining section is "proper", and, if a result of

ALL INFORMATION CONTAINED HEREIN IS UNCLASSIFIED

At
out

Mont

10

15

20

25

a light emitter for being controlled by the controller to emit light in timing with an image pickup

timing of the image pickup device; and

an auto-focussing unit for driving an optical system to focus on an object.

7. An image pickup device according to claim 6,
5 wherein

At cont
when a result of the determination of the determining section is "not proper", the controller obtains a light quantity of the light emitter which is assumed to be "proper" based on the electric signal converted by the image pickup unit, dispatches an image pickup instruction again to the image pickup unit, and at the same time, controls the light emitter to emit light in timing with the image pickup timing.

8. An image pickup device according to claim 7,
15 wherein

the controller obtains a light emission quantity of the light emitter by referring to information of a distance to an image pickup object obtained by an auto-focussing operation.

9. An image pickup device according to claim 7,
20 wherein

the controller makes the light emitter carry out a first light emission in a light emission quantity of the light emitter set by a user manual operation.

10. An image pickup method using a light emitter,
25 comprising the steps of:

carrying out a first light emission of a light

